

rasostuck

pasta

Ready-to-use
stucco filler



GYPSUM-BASED | RENDERS



Rasostuck Pasta

Ready-to-use stucco filler



TECHNICAL FEATURES

Compliant with UNI EN 13279 - class 1



Theoretical yield	~ 1,7 Kg/m ² for 1 mm thick
Apparent specific weight	~ 1,7 Kg/lit
Granulometry	≤ 0,100 mm
Sanding	after 8 - 10 hours

Laboratory tests performed at + 20°C and R.H. 65%, data subject to variations in different atmospheric and installation conditions.



METHOD OF USE

Rasostuk is a ready-to-use smoothing compound for interior finishes, allowing skim coating of walls and ideal for preparing plasterboard, gypsum partitions and cellular concrete blocks for painting. Exceptional filling power, extreme ease of application, and perfect sandability.



WARNINGS

Do not add additives or aggregates of any kind.
Do not apply on inconsistent, dusty or degraded, frozen or wet substrates.
Do not apply at temperatures below + 5 ° C or above + 35 ° C.
Do not apply in conditions of intense sun, high wind possible rain.
Keep the product in the bags intact, on pallets and in a dry and ventilated place.



PACKAGING

Bucket of 20 or 4 Kg.

*The above information is to be considered indicative, non-binding and subject to change without notice.
Therefore the suitability of the product for the desired result must be verified by the user, who is fully responsible for its use.*