

brunelleschi

ACRYLIC PRIMER

Alkali-resistant acrylic fixative insulator
ideal for the treatment of primers
that present.


Application



by brush



by roller



by spray

Brunelleschi

Acrylic primer



TECHNICAL FEATURES

Theoretical yield	~ 0,100 Lt/m ²
Specific weight	~ 1,00 Kg\Lt
PH	> 8,50
Dry residue	30%
Alkali resistance	High
Aging resistance	High
Classification by final use	Conservation and Protection

Laboratory tests performed at + 20 ° C and R.H. 65%, data subject to variations in different atmospheric and installation conditions.



METHOD OF USE

The walls should be dry and mature, free from dust and dirt. Traces of oils, waxes, fats, oily substances, salts, etc. must be removed as appropriate. Any old paints must be eliminated by scraping and brushing, and if necessary by stripping paint. In the case of new plasters, wait 4 weeks before applying the insulation in order to wait for the complete seasoning of the supports. The application can be done by roller, brush or spray depending on the surfaces to be consolidated. Shake the product well before use and dilute with water in the ratio 1 : 1 by volume.



AVVERTENZE

The chromatic aspect may vary according to the absorption of the support and the climatic conditions.

Do not apply on inconsistent, dusty or degraded, frozen or wet substrates.

Do not apply at temperatures below + 5 ° C or above + 35 ° C.

Do not apply in conditions of intense sun, high wind or possible rain.

Keep the product in the bags intact, on pallets and in a dry and ventilated place.



PACKAGING

Plastic tanks of Lt. 25, 10, 5

The above information is to be considered indicative, non-binding and subject to change without notice.

Therefore the suitability of the product for the desired result must be verified by the user, who is fully responsible for its use.